



Metal Film Precision Resistors

Type: CSR

Features:

- Thin Film Technology
- High Stability
- Low TCR: $\pm 10 \text{ ppm}/^\circ\text{C}$
- Precision Tolerance to 0.1%
- Leadfree and RoHS compliant

Dimensions:



Type	L	D	k
CSR 0204	$3.45^{\pm 0.3}$	$1.35^{\pm 0.2}$	$0.6^{\pm 0.1}$
CSR 0207	$5.9^{\pm 0.3}$	$2.2^{\pm 0.2}$	$1.0^{\pm 0.1}$

Dimensions in mm

Technical data – depending on size:

Type	Power rating P_{70}	Max. Working Voltage	Resistance Range (Ω)
CSR 0204	1/4 W	200 V	0R1 – 10M
CSR 0207	1/2 W	300 V	0R1 – 10M

High Power technical data-depending on size:

Type	Power rating P_{70}	Max. Working Voltage	Resistance Range (Ω)
CSR 0204	1/2 W	300 V	0R1 – 10M
CSR 0207	1 W	500 V	0R1 – 10M

Technical data - general:

Tolerances	0.1%, 0.25%, 0.5%, 1%, 5%
Temperature coefficient (ppm/ $^\circ\text{C}$)	± 10 , ± 15 , ± 25 , ± 50 , ± 100
Temperature range	-55°C ... $+155^\circ\text{C}$
Climatic category acc. to IEC 60068	55/155/56
Overload test (2.5x rated voltage / 5sec on, 45sec off, 10 cycles)	$\Delta R \pm 0.1\%$
Endurance test (P_{70} 0.5h on/off, 1000h)	$\Delta R \pm 0.25\%$

Issue 02/07