

NPN SILICON RF POWER TRANSISTOR

DESCRIPTION:


The **ASI 1005** is Designed for General Purpose Class C Power Amplifier Applications up to 1500 MHz.

FEATURES:

- $P_G = 12$ dB min at 5 W/ 1,000 MHz
- Hermetic Microstrip Package
- **Omnigold™** Metalization System

MAXIMUM RATINGS

I_C	600 mA
V_{CC}	35 V
P_{DISS}	18.75 W @ $T_C \leq 50^\circ C$
T_J	$-65^\circ C$ to $+200^\circ C$
T_{STG}	$-65^\circ C$ to $+200^\circ C$
θ_{JC}	15 $^\circ C/W$

PACKAGE STYLE .250 2L FLG


DIM	MINIMUM inches / mm	MAXIMUM inches / mm
A	.028 / 0.71	.032 / 0.81
B	.740 / 18.80	
C	.245 / 6.22	.255 / 6.48
D	.128 / 3.25	.132 / 3.35
E	.125 / 3.18	
F	.110 / 2.79	.117 / 2.97
G	.117 / 2.97	
H	.560 / 14.22	.570 / 14.48
I	.790 / 20.07	.810 / 20.57
J	.225 / 5.72	.235 / 5.97
K	.165 / 4.19	.185 / 4.70
L	.003 / 0.08	.007 / 0.18
M	.058 / 1.47	.068 / 1.73
N	.119 / 3.02	.135 / 3.43
P	.149 / 3.78	.187 / 4.75

ORDER CODE: ASI10524
CHARACTERISTICS $T_C = 25^\circ C$

SYMBOL	TEST CONDITIONS			MINIMUM	TYPICAL	MAXIMUM	UNITS
BV_{CBO}	$I_C = 1$ mA			45			V
BV_{CER}	$I_C = 5$ mA	$R_{BE} = 10 \Omega$		45			V
BV_{EBO}	$I_E = 1$ Ma			3.5			V
I_{CBO}	$V_{CB} = 28$ V					1.0	mA
h_{FE}	$V_{CE} = 5.0$ V	$I_C = 200$ mA		15		120	---
C_{ob}	$V_{CB} = 28$ V	$f = 1.0$ MHz				6.5	pF
P_G	$V_{CC} = 28$ V	$P_{OUT} = 5.0$ W	$f = 1.0$ GHz	12			dB
η_C				50			%